

# Orbotech Nuvogo<sup>™</sup> 80F/80FXL

Mass Production, Fine Line Direct Imaging (DI)

## Orbotech Nuvogo 80F/80FXL

Orbotech Nuvogo 80F/80FXL is a mass production direct imaging solution, optimized for HDI, flex and rigid-flex PCBs. With KLA's field-proven Large Scan Optics (LSO)™ Technology, MultiWave Laser™ Technology and advanced scaling algorithms, Orbotech Nuvogo 80F/80FXL ensures high imaging quality and accuracy. It enables high capacity of up to 7,000 panels per day per line, reducing the total cost of ownership (TCO) while maintaining optimal quality at a high speed.



## **Benefits**

## **Mass Production Digital Imaging**


- High capacity: up to 7,000 panels/day/line
- Fast target acquisition ensuring high efficiency
- Optimized imaging time with dual table transport mechanism


## **High Imaging Quality**

- Unique optics design for optimal line structure down to 15/15µm L/S
- High depth-of-focus (DOF) for challenging topographies
- Advanced scaling modes for optimal registration (±10μm)

### **High Efficiency**


- Compatible with a wide range of resists and processes
- Effective job queue management for maximum productivity
- Automation ready for seamless production











# **Technologies**




**LSO**™Technology




**MultiWave Laser**™ Technology




## High Imaging Quality



Superior line structure in a single scan enabled by KLA's  $\mathsf{LSO}^\mathsf{m}$  technology




High Depth-of-Focus (DOF) for challenging topographies



On-the-fly target recognition and acquisition


# High Resists Flexibility



Compatibility with a wide range of resists and processes driven by KLA's MultiWave Laser™ technology

# **Advanced Scaling Modes**

- Wise Scaling best scaling mode for mass production, achieving highest panel unification in the batch
- Auto scaling/fixed scaling/group scaling
- Partial Scaling sub-area registration for thin core layers
- Extremely fast target acquisition enables minimum throughput loss



# **Traceability**

Enables panel tracking by marking: serial number stamp; sub-panel and PCB; date and time stamp; scaling stamp and machine ID by alphanumeric stamping or 1-D/2-D barcode (Data Matrix Code).



# **Specifications**

### Orbotech Nuvogo 80F

### Orbotech Nuvogo 80FXL

Maximum Throughput*	<b>300 prints/h</b> Imaging Size 24" x 18"	290 prints/h Imaging Size 25" x 18"
Minimum Line/Space*	15/15µm	
Address Resolution	1.5µm	
Registration Accuracy FtG**	±10μm	
Side-to-Side Registration FtB**	20µm	
Maximum Substrate Size	635mm x 660mm 25" x 26"	660mm x 812mm 26" x 32"
Maximum Exposure Area	609.6mm x 660mm 24" x 26"	635mm x 812mm 25" x 32"
Substrate Thickness	0.025mm - 8mm	
Imaging Energy Range	10 - 2,200mJ/cm <sup>2</sup>	

<sup>\*</sup> Dependent on resist type and process

The above specifications are subject to change without notification.

<sup>\*\*</sup> All values are 30, any panel size, 4 targets